



## **Fire Storm**

# The Strongest Stripper for Extreme Build-Ups



- Effective at removing 20-50 coats!
- Liquefies finish, doesn't gum up pads.
- More than 55% active.
- No Neutralizing Required.







### FIRE-STORM Super Strength Stripper



**Description:** Fire-Storm is the highest strength stripper available on the market today. Fire-Storm is designed to remove heavy finish buildups fast, leaving floors completely stripped the first time. Firestorm attacks and liquifies heavily burnished finishes without gumming up, making pickup of stripping solution easy with a wet dry vacuum or autoscrubber. Firestorm does not leave an alkali residue, so neutralizing is not necessary.

#### **High Level of Actives**

- Maximum Strength Available in a Stripper
- · Fast and Complete Stripping of Finish
- Emulsified finish stays liquefied, doesn't gum up pads.
- Rinse Free No Neutralizing Required

#### Directions:

- 1. For heavier build-up use 1 part Fire-Storm to 4 parts cool water. 32oz/gallon (236ml/liter) For light to medium build-up, use 1 part Fire-Storm to 16 parts water. 8 oz/gallon (59ml/liter)
- 2. Apply to a manageable area. Caution: treated areas may become slippery.

3. Allow solution to react for 5 to 10 minutes -DO NOT ALLOW SOLUTION TO DRY ON FLOOR. Scrub with a floor machine or autoscrubber equipped with stripping pads. Doodle Bug around edges, etc.

4. Pick up spent solution with wet/dry vacuum or automatic scrubber.

Warning: Not for use on linoleum, asphalt tile or rubber tile floors. Wear water repellant/slip resistant footwear. Wear rubber gloves and safety eyewear to prevent skin/eye contact when using by hand. Ventilate enclosed areas to prevent excessive exposure to vapors.

> Fire-Storm labeling has easy to follow instructions in three languages.





Fire-Storm contains over 50% actives, penetrates and emulsity multiple coats of floor finish.

#### **Properties**

Appearance	Clear liquid
Odor	Lemon
% Active	50-55% by weight
pH (conc)	11 - 12
pH (1:4)	10.5 - 11.5
Dilutions	
	1:16 Light Stripping*
Water Temp. (cool)	60-80°F
Storage Stability	1 year normal conditions
Freeze Thaw	Passes 3 cycles
Flash Point	> 146°F

\*Fire-Storm is a cold water stripper. DO NOT use warm or hot water.

VOC compliance:

EPA, CA, IL, IN, MI, OH, OTC, UT, and Canadian regulations.



600 Cardigan Road Shoreview, Minnesota Phone 651-481-1900 Web www.multi-clean.com



#### Packaging

55 gallon drum, 906937 2 x 2.5 gallon case, 906935