

# Defoamer

## Silicone-Based Defoamer/Anti-Foam



DEFOAMER is a silicone-based defoamer formulated to effectively control foam generated during carpet extraction cleaning.

DEFOAMER should be applied directly to the recovery systems of carpet extraction equipment, wet vac's or autoscrubbing machines.

Note:

DO NOT ADD DEFOAMER TO SOLUTION TANK OR DIRECTLY TO CARPET.

### **DIRECTIONS:**

SHAKE WELL BEFORE USE.

1. For best results to control foam, add 2-3 ounces of DEFOAMER to 1-2 qts. of warm water (15-25 ml/liter) and mix.
2. Remove hose from wand and vacuum DEFOAMER solution into recovery tank.
3. Reconnect hose to wand.
4. Or add 2 oz. and 1/2 gallon (15 ml/litre) of water to vacuum recovery tank and mix slightly.
5. If carpet has been shampooed often, additional DEFOAMER may be required to control foam.



**DEFOAMER should be applied directly to the recovery systems of carpet extraction equipment, wet vac's or autoscrubbing machines.**

### **Properties**

Appearance .....	Milky white, slightly viscous liquid, mild odor.
pH .....	6 - 8
Specific Gravity.....	1.00
Flashpoint.....	None
Dilution.....	Use 2 ounces in 1/2 gal/warm water per recovery tank
Phosphate Free.....	Yes
Storage Stability .....	Excellent, 1 year minimum
Freeze-Thaw Stability.....	Will freeze - usable after thawing with no change in performance. Agitate after thawing and before use.

VOC Compliant - VOC Free

**Learn More.....at [www.multi-clean.com](http://www.multi-clean.com)**

Training materials: Multi-Clean Method Bulletin 1401, "Carpet Care" provides detailed carpet care procedures.



**Multi-Clean®**  
Your Guide to Clean

600 Cardigan Road,  
Shoreview, Minnesota 55126  
Phone 651-481-1900  
Fax 651-481-9987  
Web [www.multi-clean.com](http://www.multi-clean.com)

### **Packaging**

1 gallon, 910543