RSB Finish Maintainer



Versatile

A multiple use finish restorer formulated for high and ultra high speed floor care systems. R.S.B. can be used with all Multi-Clean floor finishes.

Easy to Use

R.S.B. can be used as a mop-on restorer, as a high speed spray burnishing compound, or as a cleaner restorer through an automatic scrubber.

Labor Saver

Quick and easy to apply, R.S.B. restores the "wet look" on floors while providing excellent scuff, scratch and black heel mark resistance.

An Ultra High Speed Maintenance Program utilizing PRIME SHINE and R.S.B. will greatly prolong the periods between costly stripping operations thus reducing your overall labor costs.

Learn More......at www.multi-clean.com *Training materials: Multi-Clean Method Bulletin 1415 provides detailed floor care procedures. *Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applier. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proted defective. No person has authority to waive these disclaimes or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.



RSB exceeds slip resistance when tested according to ASTM D-2047. (James Machine)

Properties

Appearance	Light blue emulsion
pH	
Flashpoint	
Specific Gravity	
Non-Volatile (solids content)	
Hardness	Soft
Slip Resistance	Passes ASTM D2047
Dilution: Spray burnish	1:8 (16 oz. per gallon)
Mop on	
Autoscrub	1:64 (2 oz. per gallon)
Repairability	Excellent
Spray Burnishing	Excellent
Leveling Ability	Excellent
Drying Time	Approx. 20 minutes
Minimum Application Temperature	
Storage Temperature	40°F minimum, 100°F max
Storage Stability	Excellent, 1 year normal cond
Freeze-Thaw Stability	Passes three cycles
VOC (minus water)	6.9% (70g/L)

VOC compliance:

EPA, CA, IL, IN, MI, OH, OTC, UT, and Canadian regulations.

Packaging 55 gallon, 904927 5 gallon, 904925 1 gallon, 904923



600 Cardigan Road Shoreview, Minnesota Phone 651-481-1900 Fax 651-481-9987 Web www.multi-clean.com