

# Splendor®

## Versatile Performance Floor Finish



### Exceptional Durability: Floors Look Better . . . Longer

Find out what loyal users have known for years; SPLENDOR keeps it shine longer, resists scuffs and black marks, all with less maintenance resulting in savings of time and money.

### Brilliant Gloss . . . Exceptional Clarity

SPLENDOR produces a high shine with clarity that produces sharp, distinct mirror images. This high shine and clarity produces a more brilliant gloss that enhances a floor's appearance. Use on all types of resilient tile as well as terrazzo type floors.

### Lasting Beauty

SPLENDOR produces a water clear film, which is especially important for today's light colored floors. With proper maintenance, stripping and recoat cycles can be further extended.

### Easy to Use . . . Easy to Apply . . . Spectacular Results

SPLENDOR goes down smooth and easy with no mop drag and levels perfectly. The product dries fast and recoats easily for trouble-free performance time after time.

### Versatile Performance

SPLENDOR can be used in high speed maintenance programs using battery, electric or propane machines. It also works well with low speed spray buffing using Buff N Clean.

Designed with black mark resistant technology!



Learn More.....at [www.multi-clean.com](http://www.multi-clean.com)

\*Training materials: Multi-Clean Method Bulletin 1415 provides detailed floor care procedures.

\*Calculators: Easy online calculator provides estimates of product usage for a project.



**Splendor exceeds slip resistance standards when tested according to ASTM D-2047 (James Machine).**

#### Properties

Appearance .....	Milky white liquid
Drying Time .....	15 - 30 minutes
Color of Dry Film.....	Water clear
Non-Volatile (solids).....	19 ± .5%
pH.....	9.0 - 9.3
Weight/Gallon .....	8.55 - 8.65
Slip Resistance.....	Exceeds .5 static coefficient of friction
Coverage .....	2000 - 4000 sq./ft./gallon
Finish Type .....	Versatile
Application Temperature...	50° F (minimum)
Storage Temperature.....	40° F minimum, 100° F maximum
Storage Stability .....	1 year under normal conditions
Freeze-Thaw Stability.....	Passes three cycles
VOC Compliant - VOC Free	

#### Packaging

55 gallon, 904887  
5 gallon, 904885  
1 gallon, 904883



600 Cardigan Road  
Shoreview, Minnesota  
Phone 651-481-1900  
Web [www.multi-clean.com](http://www.multi-clean.com)