



**Multi-Clean®**  
Your Guide to Clean

# Endura-Shine

## Rejuvenator & Protector



- Restores Shine Without Build Up
- Maximum Scuff and Scratch Resistance
- Makes Flooring Easier to Clean






# Endura-Shine

## Rejuvenator & Protector



Endura-Shine is an anti-slip protector and rejuvenator for luxury vinyl flooring (LVT) and other resilient surfaces. It restores shine, covers scratches and blemishes, and makes flooring easier to clean.

- 
**Restores Shine**  
 Brings back the lustre while hiding scratches and blemishes.
- 
**Protects Flooring**  
 Endura-Shine helps protect from daily wear and tear.
- 
**Easier to Clean**  
 Surfaces are easier to clean and stay clean.

### DIRECTIONS:

1. Deep clean flooring using Zyme-X at 1:32 (4 oz/gallon).
2. Rinse cleaned floor with plain water (scrub or mop).
3. Dilute Endura-Shine 1:4 (32 oz/gallon, first application).
4. Apply a thin coat of Endura-Shine using a rayon string mop, allow to dry 10 - 20 minutes.
5. Maintain daily by cleaning with Zyme-X.
6. Additional applications of Endura-Shine, dilute 1:8 (16 oz/gallon).

Note: On textured or embossed flooring, do not use a flat mop.

**Rubber floors: use regularly on flat and studded rubber floors.**

**Synthetic gym floors: use to protect flooring from marks and scuffs.**



**Floor Coating and Finishing Material  
As To Slip Resistance Only SA45311**



600 Cardigan Road  
Shoreview, Minnesota  
Phone 651-481-1900  
Fax 651-481-9987  
Web www.multi-clean.com



**Endura-Shine exceeds slip resistance when tested according to ASTM D-2047. (James Machine)**

### Properties

|                                       |                                     |
|---------------------------------------|-------------------------------------|
| Appearance .....                      | Light blue emulsion                 |
| pH .....                              | 9.2 - 9.3                           |
| Flashpoint .....                      | None                                |
| Specific Gravity.....                 | 1.021 - 1.025                       |
| Non-Volatile (solids content) .....   | 17 - 18% by wt.                     |
| Hardness .....                        | Soft                                |
| Slip Resistance .....                 | Passes ASTM D2047                   |
| Dilution: .....                       | 1:4 (32 oz. per gallon)             |
| Repairability .....                   | Excellent                           |
| Leveling Ability .....                | Excellent                           |
| Drying Time .....                     | Approx. 20 minutes                  |
| Minimum Application Temperature ..... | 50°F                                |
| Storage Temperature .....             | 40°F minimum, 100°F max             |
| Storage Stability .....               | Excellent, 1 year normal conditions |
| Freeze-Thaw Stability .....           | Passes three cycles                 |
| VOC (minus water).....                | 6.9% (70g/L)                        |

[www.multi-clean.com](http://www.multi-clean.com)



### Packaging

4 x 1 gallon case  
904863